

DE Dual Slurry Mixing Tank



Typical Applications

- Well Completion Fluids
- Gravel Pack Fluids
- Well-Over Fluids

Approvals

All Filtration Equipment is approved and certified by DNV to DNV 2.7-1 / BS EN 12079

Description

Clean completion fluids can only be obtained by using the right selection of filtration equipment and consumables. Diatomaceous Earth (D.E.) filtration is an effective method for filtration of completion fluids.

By selecting the Centurion Fluid Filtration's Dual Press Mix Tank system, the unit allows you to minimise deck space, whilst having the capability to service two filter presses. The unit houses both body feed, pre-coat pumps, all within the envelope of the skid.

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**

Technical Specifications

General Specifications	
Tank	316 L Stainless Steel
Capacity	30 bbl / minute
Working Pressure	7 Bar
Design Pressure	100°C
Interconnection Pipework	4" Diverting Manifold c/w Bypass (6" pipework available on request)
Body Feed	1.5" Air Driven Pump
Pre-Coat	3" Air Driven Pump
Mixing Method	1" Air Agitation Line
Flow Meter	Optional
Drain	3" Pipework
Weight (kgs)	4,000
Dimensions (mm)	3,600 x 2,214 x 1,990

For more information on our products and services, please contact your local Centurion Fluid Filtration representative or email us at CFFUK@centuriongroup.co.uk.



**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**