

4" X 4" Diesel Driven Pump



Approvals

All Filtration Equipment is approved and Certified by DNV to DNV 2.7-1 / BS EN 12079

Description

Diesel-driven centrifugal pumping units provide reliable fluid-transport performance and are housed in a protective, compact, and robust DNV approved certified skid.

The sturdy construction of the unit gives it the necessary protection against the elements associated with an oilfield environment as well as the added protection required when in transit to different rig site locations.

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**

Technical Specifications

| General Specifications | |
|----------------------------|--------------------------------------------------------|
| Pump | 4" x 4" Self-Priming Gorman Rupp |
| Engine | Deutz F3L Air Cooled |
| Starter | Air Start (Optional spring start available on request) |
| Size | 4" x 4" |
| Maximum Operating Pressure | 95 PSI |
| Recommended Flow Rate | 184 m ³ / hr (810 gpm) |
| Maximum Head | 130 ft |
| Day Tank | 246 Litres (65 Gallons) |
| Weight (kgs) | 2,500 |
| Dimensions (mm) | 2,600 x 1,360 x 1,820 |

For more information on our products and services, please contact your local Centurion Fluid Filtration representative or email us at CFFUK@centuriongroup.co.uk.



**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**