

EN160 Oilbond Filter Cartridge



Description

The media in this unique absorbent cartridge efficiently and economically removes free, emulsified and dissolved oils in many process fluids reclamation and disposal applications.

Oilbond exhibits very low clean pressure loss which gradually increases as the element becomes loaded providing a positive indication of cartridge change out time.

Typical Applications

- Industrial Discharge Water
- Bilge Water
- Surface Water Runoff

Benefits

- Manufactured at Centurion Fluid Filtration Production Facilities
- Designed for oilfield & Industrial applications
- Thermal bonded (welded) end caps
- Reduces hydrocarbon levels to meet regulatory discharge standards
- Absorbed hydrocarbons are chemically bound by the media and not leachable
- High integrity construction
- Cartridges are completely incinerable

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**

Technical Specifications

General Specifications	
Filter Media	Centurion Fluid Filtration Modified Polymer Blend
Filter Diameter	6.5" (165 mm)
Filter Length	40" (1,005 mm)
Seal Material	Buna, EPDM, Viton & Nitrile
End Cap Details	A range of end fittings are available
Recommended Operating Conditions	
Max. Temperature	70°C at 20 psid
Max. Flow Rate	3.4 m³/hr per 40" Filter

Media OB - Centurion Fluid Filtration Modified Polymer Blend	Filter Length 40" - 1,005mm 30" - 755mm	Seal Material E - EPDM N - Nitrile B - Buna V - Viton	End Fitting 2 - Flat / 226 Others on Request
---	--	--	--

Cartridge Coding: EN160 - OB 40 N 2

For more information on our products and services, please contact your local Centurion Fluid Filtration representative or email us at CFFUK@centuriongroup.co.uk.

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**