

EN65 Activated Carbon Filter Cartridge



Description

Activated carbon is a highly effective way of targeting dissolved oils, chlorinated hydrocarbons, degradation products and many other organic impurities that can be present in process fluids.

Granular Activated Carbon (GAC) filter elements provide one of the most efficient ways to target a wide range of industrial contaminants and remove them from a variety of process fluids. Activated carbon used in our filter elements is a time and cost-effective solution for targeting residual contaminants.

Typical Applications

- Industrial Discharge Water
- Bilge Water
- Surface Water Run Off
- Process Water
- Amines
- Glycol

Benefits

- Manufactured at Centurion Fluid Filtration production facilities
- Quick and easy change out
- Reduces hydrocarbons and other contaminants present
- Cartridge canister offers a quick change out alternative solution to media beds
- High integrity construction

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**

Technical Specifications

General Specifications	
Filter Media	Granular Activated Carbon
Filter Diameter	2.5" (65 mm)
Filter Length	40" (1,005 mm), 30" (755 mm)
Seal Material	Buna, Neoprene, EPDM, Viton & Nitrile
End Cap Details	A range of end fittings are available
Recommended Operating Conditions	
Max. Temperature	82°C
Max. Flow Rate	1 m ³ /hr per 40" Filter

Media GAC - Granular Activated Carbon	Filter Length 40" - 1,005mm 30" - 755mm	Seal Material E - EPDM N - Nitrile B - Buna V - Viton	End Fitting 3 - Flat / 222 Others on Request
--	--	--	--

Cartridge Coding: EN65 - AG 02 40 N 3

For more information on our products and services, please contact your local Centurion Fluid Filtration representative or email us at CFFUK@centuriongroup.co.uk.

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**