

Industrial Hard Wall Suction and Delivery Hoses



Description

The Centurion Fluid Filtration industrial hard wall suction and delivery hoses are suitable for use with a wide range of services.

They are constructed from Nitrile (NBR) rubber, reinforced with high strength synthetic cord, antistatic copper wire and steel helix wire. Finished with a coating of smooth black synthetic rubber.

Our hoses are resistant to weathering, they are also compatible with fluids containing up to 30% aromatic content. Each assembly terminations comes with King Combination [KC] nipples and swaged ferrules.

Typical Applications

- Well Completion Fluids
- Brines
- Work-Over Fluids
- Waste Water
- Pre-Filtration
- Seawater

**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**

Technical Specifications

Hose Specifications

Working Pressure 150 psi (10.34bar)

Temperature range -20°C to 70°C

ID	Working Pressure		Nominal Weight		Bend Radius	
	inch	bar	psi	Kg/m	Lbs/ft.	mm
1		10	150	1.44	0.97	250
2		10	150	1.85	1.24	330
3		10	150	3.18	2.13	500
4		10	150	5.07	3.40	700
6		10	150	10.97	7.36	1,200

For more information on our products and services, please contact your local Centurion Fluid Filtration representative or email us at CFFUK@centuriongroup.co.uk.



**DELIVERING SAFE AND INNOVATIVE SOLUTIONS TO MEET
PRODUCTION AND PROCESS NEEDS.**