

## 300CFM HP Rigsafe Framed Compressor



### Technical Specifications

#### Performance

Free Air Delivery	M3/MIN (CFM)	8.5 (300)
Rated Operating Pressure	BAR (PSI)	14.0 (200)
Maximum Operating Pressure	BAR (PSI)	15.5 (225)

#### Engine Data

Make	JOHN DEERE
Model	4045HF285
Power	93KW 125HP
Number of Cylinders	4
Rated Speed	2,200 RPM

Doosan Model 14/85

**AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.**

### Dimensions

Overall Length	3,400 mm
Overall Width	1,800 mm
Overall Height	1,800 mm
Weight	4,100 Kgs
Fuel Tank Capacity	219 Litres
Running Time at Full Load	10 Hrs
Air Outlets	3 x ¾" and 1 x 2"

### Special Features

- DNV 2.7-1 specification frame c/w built in bunded base
- Fitted with air inlet shutdown control
- Exhaust gas spark arrestor
- Braided fuel lines
- Anti-static cooling fan & belts
- 110v shutdown
- Acoustic enclosure

**Full certification provided.**

Note: The above referred specifications are our minimum standard and for guidance purposes only. For compressor specific information applicable to comply with region specific standards, please consult your local Centurion Power & Equipment representative.

For more information on Compressors, please contact your local Centurion Power & Equipment representative or email us at [CPEUK@centuriongroup.co.uk](mailto:CPEUK@centuriongroup.co.uk).

**AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.**