

425CFM 7/120 Rigsafe Mobile Compressor



Technical Specifications

Performance

Free Air Delivery	M3/MIN (CFM)	12.0 (425)
Rated Operating Pressure	BAR (PSI)	7.0 (100)
Maximum Operating Pressure	BAR (PSI)	8.6 (125)
Safety Valve Setting	BAR (PSI)	10.3 (150)

Dimensions

Length (fixed height)	4,120 mm
Width	1,985 mm
Height	1,693 mm
Ground Clearance	250 mm
Weight (net) fixed/adjustable	1,935/1,965 Kg
Weight (working) fixed/adjustable	2,121/2,151 Kg

AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.

Engine Data	
Make	JOHN DEERE
Model	4045HF275
No. of cylinders	4
Full Load Speed	2,400 rpm
Power	93 kW 125 HP
Electrical - volts	24
Cooling	Water
Fuel Tank Capacity	219 Litres
Air Outlets	1 x 2" and 3 x ¾"

Sound Level Data	
Fully compliant to outdoor noise directive 2000/14/EC (2006)	99

Tyre Size	
Tyre size	205/75 R16
Number of wheels	2

Special Features

- Bunded base
- Fitted with air inlet shutdown control
- Exhaust gas spark arrestor
- Braided fuel lines
- Anti-static cooling fan & belts
- Acoustic enclosure
- 110v shutdown

Full certification provided.

Note: The above referred specifications are our minimum standard and for guidance purposes only. For compressor specific information applicable to comply with region specific standards, please consult your local Centurion Power & Equipment representative.

For more information on Compressors, please contact your local Centurion Power & Equipment representative or email us at CPEUK@centuriongroup.co.uk.

AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.