

## 450CFM 10/125 Rigsafe Framed Compressor



### Technical Specifications

#### Performance

Free Air Delivery	M3/MIN (CFM)	12.7 (450)
Rated Operating Pressure	BAR (PSI)	10.3 (150)
Maximum Operating Pressure	BAR (PSI)	12.1 (175)

#### Dimensions

Overall Length	3,700 mm
Overall Width	2,000 mm
Overall Height	2,100 mm
Weight	4,400 Kgs
Fuel Tank Capacity	276 Litres
Running Time at Full Load	10 Hrs
Air Outlets	1 x 2" , 1 x 1 1/4" , 2 x 3/4" BSPT

**AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.**

Engine Data	
Make	JOHN DEERE
Model	6068HF285
Full Load Speed	2,400 rpm

### Special Features

- DNV 2.7-1 specification frame c/w built in bunded base
- Fitted with air inlet shutdown control
- Exhaust gas spark arrestor
- Braided fuel lines
- Anti-static cooling fan & belts
- Acoustic enclosure
- 110v shutdown

**Full certification provided.**

Note: The above referred specifications are our minimum standard and for guidance purposes only. For compressor specific information applicable to comply with region specific standards, please consult your local Centurion Power & Equipment representative.

For more information on Compressors, please contact your local Centurion Power & Equipment representative or email us at [CPEUK@centuriongroup.co.uk](mailto:CPEUK@centuriongroup.co.uk).



**AIR, STEAM AND POWER SOLUTIONS FOR CRITICAL INDUSTRIES.**