

22kW Standard Tooling Hydraulic Power Unit



Key Features

- Manufactured in accordance with DNV 2.7-1
- Sacrificial weld plates supplied on unit
- Can be supplied with auxiliary pressure and flow control valves to suit client requirements
- Pressure, return and drain line filtration.

Description

The 22kW Standard Tooling Hydraulic Power Unit is suited to operate a wide range of tooling and used for various applications. It is operator friendly with a basic control function and is fitted with a low level and overheat protection.

What's Included

- Operating Manual
- Industry Standard $\frac{3}{4}$ " Wing Type Hydraulic Connectors for Pressure and Return
- ISO B Connection for Case Drain
- Crowfoot Connection for Bowman Cooler
- Supplied With 20m Electrical Cable

Model

- 22kW

SUBSEA SOLUTIONS THAT CHALLENGE CONVENTIONAL THINKING.

Specifications

Overall Specs	
Max Flow	75 l/min at 60 Hz Operation
Max Pressure	320 BAR at 35 L/MIN 50 Hz Operation
Motor	22 kW WEG, 4 pole, 3 ph, 380/440 v, 50/60 Hz
Starter	Star Delta in SS enclosure
Filtration	MP Filtri Pressure, return & drain
Reservoir	200 Litre, low oil & high temp trips
Cooling	Bowman Seawater heat exchanger
Frame	4 Point Lifting with accordance with DNV 2.7-1
Dimensions	1492 x 800 x 1615 mm
Weight	1000 kg
Certification	Full certification package for MPI, slings and load test



SUBSEA SOLUTIONS THAT CHALLENGE CONVENTIONAL THINKING.