

## HR300 Hydraulic Hose Reel



### Key Features

- Sacrificial weld plates supplied on unit
- Primary structure in accordance with DNV 2.7-1
- Can be supplied with additional drain line on request
- Pay in/out local control
- Tool hot/cold local control
- Fitted with rotary coupling.

### Description

The HR300 Hydraulic Hose Reel is used to deploy hoses, cables and umbilical for subsea operations. It is ideal for supporting our tools found in the hire fleet.

### What's Included

- Operating Manual
- Industry Standard 3/4" Wing Type Hydraulic Connectors on Downline
- Supplied With 6m Deck Whips
- Supplied as Standard with 200m Twin Line Hose

### Model

- HR300

**SUBSEA SOLUTIONS THAT CHALLENGE CONVENTIONAL THINKING.**

## Specifications

Overall Specs	
Capacity	300 m Twin Hose Umbilical
Max Pull	1000 kg
Flow	15-60 l/min
Pressure	200 bar
Connection	6 m Hose c/w Q.D Couplings
Weight	1500 kg Tare, 3000 kg Gross
Dimensions	1770 x 1770 mm
Drum Dimensions	Core: 800 mm Flange: 350 mm Width: 800 mm
Certification	Full Certification Package for Hose Test, MPI, Slings, Shackles and Load Test



**SUBSEA SOLUTIONS THAT CHALLENGE CONVENTIONAL THINKING.**